

## 3G HD-SDI Video Patchcords

**Model Number**  
PC - - -

**Patchcord Type**  
**KM** Microsize Patchcord  
**M** Midsize Patchcord  
**V** Standard Size Patchcord

**Color**  
**BLACK**  
**RED**  
**GREEN**  
**BLUE**  
**PURPLE**  
**YELLOW**  
**ORANGE**  
**WHITE**

**Patchcord Length**  
 1 1' [300mm]  
 1.5 1.5' [450mm]  
 2 2' [600mm]  
 3 3' [900mm]  
 4 4' [1.20m]  
 6 6' [1.80m]  
 10 10' [3.05m]

example... MPC-2-RED

Connectors meet or exceed 3Gb/s and utilize BELDEN 4.5GHz HD-SDI Precision Video Cable

## UHD 12G Video Patchcords

**Model Number**  
PC - - -

**Patchcord Type**  
**M4U** Micro 12G Series Patchcord  
**E8K** Super 8K+ E-Series Patchcord  
**W8K** Super 8K+ W-Series Patchcord

**Color**  
**BLACK**  
**RED**  
**GREEN**  
**BLUE**  
**PURPLE**  
**ORANGE**

**Patchcord Length**  
 1 1' [300mm]  
 1.5 1.5' [450mm]  
 2 2' [600mm]  
 3 3' [900mm]  
 4 4' [1.20m]  
 6 6' [1.80m]  
 10 10' [3.05m]

example... M4U-2-RED

Connectors meet or exceed 12G and utilize BELDEN 12GHz 4K UHD Precision Video Cable

## 3GHz 75W BNC Jack to Video Patch Plug Adapters

**AVP-SPBNC** BNC Jack to WECO Standard Size  
**AVP-MPBNC** BNC Jack to mini-WECO Midsize

- 3G SDI, HD-SDI
- Serial Digital Video
- HDTV Upgrades
- NTSC Analog

Model	Imp.	Return Loss	Center Contact (Plating)	Body (Plating)	Shield	Dielectric Insulator
AVP-SPBNC	75W	DC to 3.0GHz >26dB	Beryllium Copper (gold 3µ in. min.)	Nickel 80µ in. min.	Brass	TPE (Teflon)

## Audio Patchcords

For 110 Ohm AES/EBU Digital and Analog Audio Application

**Model Number**  
PC - - -

**Patchcord Type**  
**B** Bantam  
**L** Longframe

**Color**  
**BLACK**  
**RED**  
**GREEN**  
**BLUE**  
**YELLOW**  
**PURPLE**  
**ORANGE**  
**WHITE**

**Patchcord Length**  
 1 1' [300mm]  
 1.5 1.5' [450mm]  
 2 2' [600mm]  
 3 3' [900mm]  
 4 4' [1.20m]  
 6 6' [1.80m]  
 10 10' [3.05m]

example... BPC-2-GREEN

## 3G HD-SDI Video Patchcords/Cables

**Model Number**  
PC - - -

**Connector A**  
**BNC** BNC, male  
**BNF** BNC, female  
**HBN** HDBNC, male  
**D12** DIN 1.0/2.3, male

**Connector B**  
**KM** Microsize Patch, male  
**M** Midsize Patch, male  
**V** Standard Size Patch, male  
**BNC** BNC, male  
**BNF** BNC, female  
**HBN** HDBNC, male  
**D12** DIN 1.0/2.3, male

**Patchcord/Cable Length**  
 1 1' [300mm]  
 1.5 1.5' [450mm]  
 2 2' [600mm]  
 3 3' [900mm]  
 4 4' [1.20m]  
 6 6' [1.80m]  
 10 10' [3.05m]  
 15 15' [4.57m]  
 25 25' [7.62m]  
 50 50' [15.24m]  
 75 75' [22.86m]  
 100 100' [30.48m]

**Color**  
**BLACK**  
**RED**  
**GREEN**  
**BLUE**  
**PURPLE**  
**YELLOW**  
**ORANGE**  
**WHITE**

example... BNCPC-2-RED-BNF

Connectors meet or exceed 3Gb/s and utilize BELDEN 4.5GHz HD-SDI Precision Video Cable

## UHD 12G Video Patchcords/Cables

**Model Number**  
PC - - -

**Connector A**  
**BNCU** BNC, male  
**BNFU** BNC, female  
**HBNU** HDBNC, male  
**D12U** DIN 1.0/2.3, male

**Connector B**  
**M4U** Micro 12G Series Patch, male  
**E8K** Super 8K+ E-Series Patch, male  
**W8K** Super 8K+ W-Series Patch, male  
**BNCU** BNC, male  
**BNFU** BNC, female  
**HBNU** HDBNC, male  
**D12U** DIN 1.0/2.3, male

**Patchcord/Cable Length**  
 1 1' [300mm]  
 1.5 1.5' [450mm]  
 2 2' [600mm]  
 3 3' [900mm]  
 4 4' [1.20m]  
 6 6' [1.80m]  
 10 10' [3.05m]  
 15 15' [4.57m]  
 25 25' [7.62m]  
 50 50' [15.24m]  
 75 75' [22.86m]  
 100 100' [30.48m]

**Color**  
**BLACK**  
**RED**  
**GREEN**  
**BLUE**  
**PURPLE**  
**ORANGE**

eg... BNCU-2-RED-BNCU

Connectors meet or exceed 12G and utilize BELDEN 12GHz 4K UHD Precision Video Cable

## Stereo Bantam Patchcords

**Model Number**  
SBPC - - - RED

**Patchcord Length**  
 2 2' [600mm]  
 3 3' [900mm]

## 3 & 5 Pin XLR DMX Patchcords

**DMX512 Lighting Control Patchcords**  
 For Portable Use or Remote Environments

**Model Number**  
- - - BLACK

**Patchcord Style**

Style	Length
Neutrik Black Plated Housing with Gold contacts	
DXFM3PC-BG DMX, XLR 3 Pin, Female to Male, Neutrik Black/Gold contacts	08 8' [200mm]
DXFM5PC-BG DMX, XLR 5 Pin, Female to Male, Neutrik Black/Gold contacts	1 1' [300mm]
DXFM35PC-BG DMX, XLR 3 Pin to 5 Pin, Female to Male, Neutrik Black/Gold contacts	15 1.5' [450mm]
DXMF35PC-BG DMX, XLR 3 Pin to 5 Pin, Male to Female, Neutrik Black/Gold contacts	2 2' [600mm]
Neutrik Nickel Plated Housing with Silver contacts	
DXFM3PC-NS DMX, XLR 3 Pin, Female to Male, Neutrik Nickel/Silver contacts	3 3' [900mm]
DXFM5PC-NS DMX, XLR 5 Pin, Female to Male, Neutrik Nickel/Silver contacts	4 4' [1200mm]
DXFM35PC-NS DMX, XLR 3 Pin to 5 Pin, Female to Male, Neutrik Nickel/Silver contacts	6 6' [1800mm]
DXMF35PC-NS DMX, XLR 3 Pin to 5 Pin, Male to Female, Neutrik Nickel/Silver contacts	10 10' [3.05m]

- Features & Benefits**
- DMX512 Construction Cable
  - 120 Ohm, Low Capacitance Data Pairs
  - Meets or Exceeds USITT Standards
  - Double Shield (Foil & Braid)
  - 24 AWG Stranded TC
  - Insulation: Foam PE
  - Jacket: Flexible All-weather TPE

**3.0GHz - 3Gb/s AV-KLP**  
**Microsize Video Looping Plug**



**3.0GHz - 3Gb/s AV-DLP**  
**Midsize Video Looping Plug**



**UHD Super 8K+ W-Series**  
**Looping Plug**



**UHD Super 8K+ E-Series**  
**Looping Plug**



- Model Name: LPE8K-COLOR**
- Ultra High Definition
  - Finger grip hole for easy removal
- |        |        |
|--------|--------|
| BLACK  | GREEN  |
| RED    | BLUE   |
| ORANGE | PURPLE |
| YELLOW | GRAY   |
| IVORY  | WHITE  |